

THE MALONE PROCUT 700. 800 & 900

The Procut mowers are available in three different cutting widths. What really makes the Malone Mower a cut above the rest is the heavy duty Galvanised Frame, ensuring the long life of your machine and the Multi Banded belt prevents slipping and means that constant power is transmitted to the heavy duty cutter bar.

Another advantage of the Malone mower is the design of the lift arm brackets on the headstock, allowing a single operator to mount the mower onto the tractor quickly and easily without assistance.

The Heavy Duty Cutter Bars have five, six & seven discs respectively, each with two blades. The special Breakaway System allows the mower to swing back 45 degrees; this protects the cutting bed in the event of a collision. You also have the peace of mind that all wearing parts are readily available locally and are easily identifiable in your full colour mower manual and parts book.

The Malone ProCut 3 Point linkage mower is an excellent heavy duty machine that easily handles the tough terrain, producing a perfect clean cut every time- vital for speeding up grass recovery time.

MALONE PROCUT DISC MOWER

Malone Procut Disc Mower - 700/800/900

The Malone Procut 700, 800 & 900, 3 Point linkage mowers are one of the best selling mowers on the market. There are many mowers available on the market but not all mowers are built the same, the Malone Procut 700 / 800 / 900 mounted mowers have many desirable features and benefit that ensure you get a professional quality clean cut every time.

F PRODUCING A PERFECT CLEAN CUT EVERY TIME



Address: Malone Farm Machinery, Ballyglass, Claremorris Co. Mayo, Ireland.

Managing Director: Michael Malone Sales ROI: +353 (0)87 061 1333 Sales UK: +0044 (0)7881 344 311 International: +353 (0)94 936 0501 General Enquiries: office@malonefm.com
Sales: sales@malonefm.com
Parts & Service: stores@malonefm.com
Technical: technical@malonefm.com
Accounts: accounts@malonefm.com
Warranty: warranty@malonefm.com





	700	800	900
Cutting Width	2.1m	2.4m	2.85m
Transport Width	1.75m	1.75m	1.95m
Cutter Bar	Serviceable from top	Serviceable from top	Serviceable from top
No. of Discs	5	6	7
Blades Per Disc	2	2	2
Blade	4mm	4mm	4mm
Topping Skids	Included as standard 40mm	Included as standard 40mm	Included as standard 40mm
Swath Width	1.5m	1.8m	2.1m
Swath Wheels		2	2
Driveline	Heavy duty drive shaft / PTO Overrun / Multi- band Bel	Heavy duty drive shaft / PTO Overrun / Multiband Belt	Heavy duty drive shaft / PTO Overrun / Multi- band Belt
HP Req.	60	70	80
PTO Speed	540rpm	540rpm	540rpm
Hydraulics Req.	1 Single Acting	1 Single Acting	1 Single Acting



Address: Malone Farm Machinery, Ballyglass, Claremorris Co. Mayo, Ireland.

Managing Director: Michael Malone Sales ROI: +353 (0)87 061 1333 Sales UK: +0044 (0)7881 344 311 International: +353 (0)94 936 0501 General Enquiries: office@malonefm.com
Sales: sales@malonefm.com
Parts & Service: stores@malonefm.com
Technical: technical@malonefm.com
Accounts: accounts@malonefm.com
Warranty: warranty@malonefm.com

